


O R S E N S O



L O M I N A

IP67 Landscape lighting

LOMINA

IP67 Landscape lighting

Soft uniform spread of light in a straight pole shape housing for the perfect landscape lighting.

LOMINA holds selected LED chips that delivers a uniform spread of light from a straight pole shape housing made of Stainless Steel coated with dual layer 160micron polyester powder.

The **LOMINA** was designed with a special front cover that allows a very soft and uniform spread of light but also ensures the robustness of the product.

The **LOMINA** heat sink is designed for high rapid heat dissipation to ensure safe and long operation use.

LOMINA comes in 3 hights:

361mm for sidewalks, pathway and low flowering,


697mm for sidewalks, pathway and small bushes

1453mm for large bushes and decorative garden style

Features:

- 210 / 420 / 945 lumens
- 3 Hights
- WIDE beam angle 150°
- IP67
- High CRI >90
- Guaranteed long life time and high performance
- Perfect for landscape lighting on Outdoor installations

LOMINA is protected against water and dust and holds an Ingress Protection level of 67. It is specially designed to be mounted on the ground with a dedicated inground SPIKE to ensure strong and robust longevity.





TECHSPEC

Output		Environmental	
Type of LEDs	selected led chips	Operating Temp.	-20°C ~ 40°C / -4°F ~ 104°F
Color Temperature (K)	2700	Projected lifetime	L70 over 50,000
Luminous flux (lm)	210 (36cm)/ 420 (70cm)/ 945 (145cm)	Environment	Dry, Damp or Wet Locations, 0-100% humidity
CRI	CRI >90	Degree of protection (IP)	67
Beam angle	Wide 150°		
Efficiency (lm/w)	57 lm/W @ 2700K, 85 °C		

Electrical		Physical	
LED power (W)	3.5 (36cm)/ 7.2 (70cm)/ 16.2 (145cm)	Fixture Housing	SST 304
Fixture Input Voltage	24VDC	coating	Black Dual layer 160micron polyester powder
Driver	External Constant voltage0(not incl.)	Front cover	Optical grade PMMA
Input cable	1.0m IP rated cable	Fasteners	SST 304
		Diameter	19mm
		Hight	361mm / 697mm/ 1453mm
		Bottom Plate	3mm x 80mm Ø
		Ground Spike	300mm
		Fixture Weight(gr)	390(36cm)/ 770(70cm)/ 1154(145cm)

DIMENSIONS

